



STANDARD MATERIAL NOTES:

- #10 GA. STL. WIRE, CRIPPED & INTERWOVEN TO FORM 1 1/2" DIAMOND MESH
- 1 1/4" x 3/8" x 1/8" CHANNEL, VERTICAL FRAMING
- 1 1/2" x 1/8" CHANNEL, MORTISED & TENONED
- CENTER REINFORCEMENT CROSSBARS - CONSIST OF 1 3/8" x 1/8" CHANNELS RIVETED TOGETHER
- TOP HOZ. CAPPING BARS 1/4" x 2" PLAT SECURED TO TOP FRAMING CHANNELS 1/4" x 1/4" BOLTS & WASHERS
- BOTTOM FRAMING CHANNELS 1/4" x 1/4" BOLTS WITH RIVETS
- RIVETS ARE 1/4" DIA. & 1/2" LONG
- LATE POSTS BASE ON PROJECT REQUIREMENTS:
- 1/4" x 2" VERT. PLATS BOLTED BETWEEN CHANNEL FRAMING
- 2 1/8" x 2 1/4" STANCHIONS WELDED TO 12" x 12" x 5/16" PL.
- 2 1/8" x 1/8" STANCHION WELDED TO 12" x 12" x 5/16" FLOOR PLATE
- FLOOR SHOES SIZED TO SUIT VERTICAL FRAMING AND TO PROVIDE APPROX 3 1/2" CLEARANCE FROM FLOOR TO FLOOR

<b>ACME</b> 8001 1/2" x 1/2" x 1/2" Vertical	
EXHIBIT NUMBER	8001 1/2" x 1/2" x 1/2" Vertical
CUSTOMER	NAME
LOCATION	LOCATION
TITLE	STANDARD DUTY WOVEN WIRE DETAILS
JOB NO.	XXX
DATE	10-XX